



## **PRODUCT DATA SHEET**

### **ECO-THERM anti-condensation coating**

<b>Quality:</b>	Brush paintable
<b>Description:</b>	Dispersion-based anti-condensation coating
<b>Scope of application:</b>	Steel, stainless steel and aluminum as well as concrete and plaster surfaces.
<b>Characteristics:</b>	Insulates and prevents condensation drops
<b>Colors and Gloss:</b>	Light gray and white. Other colors on request. matt
<b>Basic information:</b>	Density 1,0g/m <sup>3</sup> Solid volume / dry weight: 33 % Drying time at 20°C and humidity 55% RF: 8-12Std. Fire class: NT Fire 004 1
<b>Consumption theoret.:</b>	1.000 grams per m <sup>2</sup>
<b>Layer thickness:</b>	1,2 mm at 1,000 grams per m <sup>2</sup>
<b>Surface underground:</b>	The substrate must be free of grease and oil. Loose particles are to be removed.
<b>Instructions for use:</b>	<u>Working temperature:</u> min. + 5° C and max. 85% RH when applying. Frost must be avoided at all costs, even during the drying phase <u>Dilution:</u> ECO-THERM is delivered ready to use. Can be diluted with up to 4% clear water if required. <u>Application:</u> with a brush, spatula or roller <u>Cleaning:</u> with water immediately after work
<b>Safety:</b>	Product-code M-DF01 (Gisbau)
<b>Storage:</b>	12 months when stored frost-free in the original packaging (unopened)
<b>Pack sizes:</b>	5kg, 10kg, 20kg bucket and 100kg barrel